

Specification

VAN GEL® ES Magnesium Aluminum Silicate

October 31, 2017

Product Code: 50210

Composition: Magnesium aluminum silicate

Physical State: Off-white granules

SPECIFICATION TEST METHOD

*Moisture Content at Shipment 8.0% maximum T-684

**Viscosity, Brookfield, 5% Dispersion #2 spindle at 60 rpm 40 - 200 cps T-678

GENERAL INFORMATION

Typical values not routinely measured or reported on the Certificate of Analysis.

pH, 5% dispersion 9.0

*Certified Property

Uses – General purpose industrial thickener and suspending agent for aqueous systems.

VAN GEL is a registered trademark of Vanderbilt Minerals, LLC.

The information presented herein, while not guaranteed, was prepared by technical personnel and, to the best of our knowledge and belief, is true and accurate as of the date hereof. No warranty, representation or guarantee, express or implied, is made regarding accuracy, performance, stability, reliability or use. This information is not intended to be all –inclusive, because the manner and conditions of use, handling, storage and other factors may involve other or additional safety or performance considerations. The user is responsible for determining the suitability of any material for a specific purpose and for adopting such safety precautions as may be required. Vanderbilt Minerals, LLC does not warrant the results to be obtained in using any material, and disclaims all liability with respect to the use, handling or further processing of any such material. No suggestion for use is intended as, and nothing herein shall be construed as, a recommendation to infringe any existing patent or to violate any federal, state or local law or regulation.